


Engineering reference data are not verified. The specifications are subject to change without notice.

Primax5 150 InGaN White: NSW-FSG



- Super high brightness surface mount LED.
- Excellent reliability with nitride phosphor system.
- Compact package outline (LxW) of 5.6 x 3.0 mm. Ultra low height profile – 1.0 mm.
- Low thermal resistance.
- Electrical and thermal isolated solder-pad design for better heat management.
- Compatible to IR reflow soldering.



Engineering reference data are not verified. The specifications are subject to change without notice.

Material

	Material
Lead-frame.	Cu Alloy With Ag Plating.
Package.	High Temperature Resistant Plastic, PPA.
Encapsulant	Silicone Resin.
Soldering Leads.	Ag Plating.

Note: This product is Pb free.

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	180	mA
Peak pulse current	200	mA
Reverse voltage.	5	V
LED junction temperature.	125	°C
Operating temperature.	-40 ... +100	°C
Storage temperature.	-40 ... +100	°C

Engineering reference data are not verified. The specifications are subject to change without notice.

Optical Characteristics at Tj=25°C.

Part Number	Luminous Flux @ If=150mA (lm)			Viewing Angle
	Min	Typ.	Max	
NSW-FSG-R3S-1	45.2	52.0	67.2	120

Flux Bin	Flux @ If = 150mA (lm)	
	Min	Max
R3	45.2	51.7
S2	51.7	59.0
S3	59.0	67.2

1. Luminous intensity is measured with an accuracy of $\pm 11\%$.
2. Color binning is carried for all units as per the wavelength-binning table. Only one color group is allowed for each reel.
3. Typical CRI of 72.


Electrical Characteristics at Tj=25°C.

Part Number	Vf @ If = 150mA		
	Min. (V)	Typ. (V)	Max.(V)
NSW-FSG	3.0	3.3	3.7

Forward voltages are tested using a current pulse of 1 ms and has an accuracy of $\pm 0.1V$.

Engineering reference data are not verified. The specifications are subject to change without notice.

Color.



Chromaticity coordinate groups are measured with an accuracy of ± 0.01 .

		1	2	3	4
0A	Cx	0.2950	0.2920	0.2984	0.3009
	Cy	0.2970	0.3060	0.3133	0.3042
0R	Cx	0.2980	0.2950	0.3009	0.3037
	Cy	0.2880	0.2970	0.3042	0.2937
1A	Cx	0.3048	0.3130	0.3144	0.3068
	Cy	0.3207	0.3290	0.3186	0.3113
1R	Cx	0.3068	0.3144	0.3161	0.3093
	Cy	0.3113	0.3186	0.3059	0.2993
2A	Cx	0.3215	0.3290	0.3290	0.3222
	Cy	0.3350	0.3417	0.3300	0.3243
2R	Cx	0.3222	0.3290	0.3290	0.3231
	Cy	0.3243	0.3300	0.3180	0.3120

Engineering reference data are not verified. The specifications are subject to change without notice.


3A	Cx	0.3371	0.3451	0.3440	0.3366
	Cy	0.3490	0.3554	0.3427	0.3369
3R	Cx	0.3366	0.3440	0.3429	0.3361
	Cy	0.3369	0.3428	0.3307	0.3245
0B	Cx	0.2920	0.2895	0.2962	0.2984
	Cy	0.3060	0.3135	0.3220	0.3133
0S	Cx	0.2895	0.2870	0.2937	0.2962
	Cy	0.3135	0.3210	0.3312	0.3220
1B	Cx	0.3028	0.3115	0.3130	0.3048
	Cy	0.3304	0.3391	0.3290	0.3207
1S	Cx	0.3005	0.3099	0.3115	0.3028
	Cy	0.3415	0.3509	0.3391	0.3304
2B	Cx	0.3207	0.3290	0.3290	0.3215
	Cy	0.3462	0.3538	0.3417	0.3350
2S	Cx	0.3196	0.3290	0.3290	0.3207
	Cy	0.3602	0.3690	0.3538	0.3462
3B	Cx	0.3376	0.3463	0.3451	0.3371
	Cy	0.3616	0.3687	0.3554	0.3490
3S	Cx	0.3381	0.3480	0.3463	0.3376
	Cy	0.3762	0.3840	0.3687	0.3616
0C	Cx	0.2984	0.2962	0.3028	0.3048
	Cy	0.3133	0.3220	0.3304	0.3207
0T	Cx	0.2962	0.2937	0.3005	0.3028
	Cy	0.3220	0.3312	0.3415	0.3304
1C	Cx	0.3115	0.3205	0.3213	0.3130
	Cy	0.3391	0.3481	0.3373	0.3290
1T	Cx	0.3099	0.3196	0.3205	0.3115
	Cy	0.3509	0.3602	0.3481	0.3391
2C	Cx	0.3290	0.3376	0.3371	0.3290
	Cy	0.3538	0.3616	0.3490	0.3417
2T	Cx	0.3290	0.3381	0.3376	0.3290
	Cy	0.3690	0.3762	0.3616	0.3538
3C	Cx	0.3463	0.3551	0.3533	0.3451
	Cy	0.3687	0.3760	0.3620	0.3554
3T	Cx	0.3480	0.3571	0.3551	0.3463
	Cy	0.3840	0.3907	0.3760	0.3687
0D	Cx	0.2984	0.3048	0.3068	0.3009
	Cy	0.3133	0.3207	0.3113	0.3042
0U	Cx	0.3037	0.3009	0.3068	0.3093
	Cy	0.2937	0.3042	0.3113	0.2993

Engineering reference data are not verified. The specifications are subject to change without notice.

1D	Cx	0.3130	0.3213	0.3221	0.3144
	Cy	0.3290	0.3373	0.3261	0.3186
1U	Cx	0.3144	0.3221	0.3231	0.3161
	Cy	0.3186	0.3261	0.3120	0.3059
2D	Cx	0.3290	0.3371	0.3366	0.3290
	Cy	0.3417	0.3490	0.3369	0.3300
2U	Cx	0.3290	0.3366	0.3361	0.3290
	Cy	0.3300	0.3369	0.3245	0.3180
3D	Cx	0.3451	0.3533	0.3515	0.3440
	Cy	0.3554	0.3620	0.3487	0.3427
3U	Cx	0.3440	0.3515	0.3495	0.3429
	Cy	0.3428	0.3487	0.3339	0.3307


Engineering reference data are not verified. The specifications are subject to change without notice.

Solder Pad Design.




Engineering reference data are not verified. The specifications are subject to change without notice.


Relative flux vs. forward current




Forward voltage vs. forward current



Radiation pattern.



Color Spectrum.




Max current vs. Ambient Temperature

Engineering reference data are not verified. The specifications are subject to change without notice.

Taping And Orientation.


Reels come in quantity of 2000 units.

Reel diameters are 180 mm.



Engineering reference data are not verified. The specifications are subject to change without notice.

Recommended Pb Free IR-Reflow Soldering Profile.



Engineering reference data are not verified. The specifications are subject to change without notice.

NOTE.

All the information published is considered to be reliable. However, DOMINANT Semiconductors does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Semiconductors reserves the right to make changes at any time without notice to any products in order to improve reliability, function or design.

DOMINANT Semiconductors products are not authorized for use as critical components in life support devices or systems without the express written approval from the managing director of DOMINANT Semiconductors.